Declaration of Performance

No. 2026/OP/01

1. **Solid wood panelling and cladding**

2 Wooden elements 12.5 - 130 x 60 - 200 mm, with or without tongue and groove and with or without profiled surface for use as interior and exterior cladding made of solid wood, in its natural state for interior and exterior wall and ceiling cladding. Product identification by label attached to the pallet packaging and on accompanying documents.

3. Dřevozpracující družstvo
Lukavec čp. 9
394 26 Lukavec
Česká republika
IČ: 00028631

5. AVPC systém 4

6a. EN 14 915:2013

7.

Essential characteristics	Classes and/or threshold levels	Harmonised technical specification
Reaction to fire	D-s2, d0	EN 14 915:2013
Density	470 kg/m^3	
Release of formaldehyde	E1	
Content of pentachlorophenol	≤ 5 x 10^{-6}	
Water vapour permeability	μ 20 / 50	
Sound absorbtion	0,1 / 0,3	
Thermal resistance	0,12 W/m.K	
Resistance to fixings	pre-drilling is not necessitate	
Durability – natural biological durability	class 4	

The performance of the product identified above is in conformity with the set of declared performance.
This declaration of performance is issued under the sole responsibility of the manufacturer identified above, in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer:

Jaroslav Vondrů, Chairman of the Board

In Lukavec 06. 02. 2026

(sign)

DŘEVO ✓ DOVEDNOST ✓ LIDÉ ✓